3

1

2

**4** 5

6

7

9

10

11

14 15

13

16 17

18

20

19

21

23

24 25

26

27

28

The following are added for clarification purposes only and do not add any new matter:

- 1. The following new paragraphs are added to the end of the list of reference numerals, such addition being made at line 5 on page 8 of the original application:
  - 22 front fold-down score line
  - 23 front fold-under score line

2. The third paragraph following the list of reference numerals on page 8, starting at line 17, is amended to read as follows:

"The present invention is assembled for use by folding the flaps as follows: with the Seating Surface, 1, situated horizontally, Side Flaps, 4, are folded up to a vertical position along the side edge of seating surface, 1, so as to be perpendicular to said seating surface, 1. Rear Portion of Side Support Flaps, 5, are folded such that they are vertical and perpendicular to the Side Flaps 4, situated along the rear edge of Seating Surface 1, adjacent to the Outside portion of back support flap, 6. The Outside portion of back support flap, 6, is folded up to a vertical position along the outside of Rear Portion of Side Support Flaps, 5, and the Inside portion of back support flap, 8, is folded down over the inside of Rear Support Flaps, 5, and the tabs, 9, are then inserted into the tab slots, 11. The seat is anchored in place by a Front, Fold-under Flap, 13, which is folded down along front fold-down score line 22, and then rearward under the adult toilet seat, 16, along front fold-under score line 23, such that the Vertical portion of Front fold-under flap, 12, covers the front edge of the toilet seat, 16 in Fig. 2, and the Front, Fold-under Flap, 13,

```
is sandwiched between the toilet seat, 16, and toilet bowl rim, 17, as
2
   shown in Fig. 2. Handles are provided by a handle flap, 14, with
   handle cutouts, 15, which are folded to a vertical position for
3
   grasping.
 5
 6
7
 8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
```